

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label) Liquid Static Inhibitor (MBI-1001)			
MANUFACTURER'S NAME Maxi-Blast, Inc		EMERGENCY TELEPHONE NO. (574) 233-1161	
ADDRESS (Number, Street, City, State and Zip Code) 3650 North Olive Road, South Bend, Indiana 46628		MANUFACTURER'S D-U-N-S NO. 03-934-9162	
MATERIAL DESCRIPTION, PROPER SHIPPING NAME Aqueous Anti-Static Solution Item 48580 Sub 3 Class 55			
HAZARD CLASSES (as applicable) Non-Regulated		CAS. NO. 9005-64-5	
CHEMICAL FAMILY Sorbitan Mono Laurate Ethoxylated		FORMULA N.A.	

SECTION II – INGREDIENTS (list all ingredients)

CAS REGISTRY NO.	Approx. %W	CHEMICAL NAME(S)	Listed as a Carcinogen in NTP, IARC or OSHA 1910(z) (specify)
9005-64-5		Sorbitan Mono Laurate, Ethoxylated	No

SECTION III – PHYSICAL DATA

BOILING POINT 212° F 100° C	N.A.	SPECIFIC GRAVITY (H ₂ O=1)	1.1		
VAPOR PRESSURE mm Hg	<1	PERCENT VOLATILE BY VOLUME (%)	0-3(H ₂ O)	PERCENT SOLID BY WEIGHT (%)	0
VAPOR DENSITY (AIR=1)	>1	EVAPORATION RATE (=1)	< 1		
SOLUBILITY IN WATER	100%	PH=	6-8		
APPEARANCE AND ODOR Yellow Liquid, Bland Odor				MATERIAL FORM: Liquid	

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

BOILING POINT 212° F 100° C	FLAMMABLE LIMITS	LEL N.A.	UEL N.A.
EXTINGUISHING MEDIA Carbon Dioxide, Dry Chemical, Water Fog or Foam.			
SPECIAL FIRE FIGHTING PROCEDURES Firefighters should wear self-contained breathing apparatus.			
UNUSUAL FIRE AND EXPLOSION HAZARDS None known.			

SECTION V – HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE – Conditions to Avoid	THRESHOLD LIMIT VALUE PERMISSIBLE EXPOSURE LIMIT <input type="text"/> <input type="text"/> N.A.
Prolonged contact with skin or eyes may cause temporary irritation.	
PRIMARY ROUTES OF ENTRY <input checked="" type="checkbox"/> Inhalation <input checked="" type="checkbox"/> Skin Contact <input checked="" type="checkbox"/> Other (specify) Eye	
EMERGENCY AND FIRST AID PROCEDURES Flush eyes 15-20 minutes with water. Wash skin with soap and water. Remove from area of	
Exposure, seek medical attention if irritation persists.	

SECTION VI – REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY(materials to avoid) Strong oxidizing material may cause a reaction.			
HAZARDOUS DECOMPOSITION PRODUCTS Carbon Dioxide, Carbon Monoxide			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID Oxidizing agents
	MAY NOT OCCUR	X	

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Us absorbent material to collect and contain for disposal.
Wash area with detergent and rinse thoroughly.	
WASTE DISPOSAL METHOD Disposal must be made according to Federal, State and Local regulations.	
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs) N.A.	
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33) N.A.	
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water) None	
<input type="checkbox"/> Theoretical _____ lb/gal	<input type="checkbox"/> Analytical _____ lb/gal

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify Type) None should be required.			
VENTILATION	LOCAL EXHAUST (Specify Rate) Not required.	SPECIAL	N.A.
	MECHANICAL (General – Specify Rate) Normal ventilation required.	OTHER	N.A.
PROTECTIVE GLOVES (Specify Type) Rubber gloves suggested.		EYE PROTECTION (Specify Type) Chemical Worker's Goggles	
OTHER PROTECTIVE EQUIPMENT None			

SECTION IX – SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Store in ventilated areas between 50° F – 120° F. Keep away from oxidizing agents, excessive heat and ignition sources.
OTHER PRECAUTIONS None	

<p>Maxi-Blast[®] Inc.</p> <p>3650 North Olive Road – South Bend, In 46628 (574) 233-1161 – Fax: (574) 234-0792 – e-mail: info @maxiblast.com MSDSMBI1001 Page 2 Rev. – 7 1/31/08</p>	
---	--