

Maxi-Blast[®] Inc.

An ISO 9001:2000 Registered Company

Plastic Blast Cleaning Medias ■ Finishing Equipment and Technology

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label) Walnut Shell Blast Media	
MANUFACTURER'S NAME Maxi-Blast, Inc	EMERGENCY TELEPHONE NO. (574) 233-1161
ADDRESS (Number, Street, City, State and Zip Code) 3650 North Olive Road, South Bend, Indiana 46628	MANUFACTURER'S D-U-N-S NO. 03-934-9162
MATERIAL DESCRIPTION, PROPER SHIPPING NAME Granulated Apricot Pit Item 175480 Class 55	
HAZARD CLASSES (as applicable) Non-Regulated	
CHEMICAL FAMILY Walnut Shell - Organic	FORMULA Natural - Organic

SECTION II – INGREDIENTS (list all ingredients)

CAS REGISTRY NO.	Approx. %W	CHEMICAL NAME(S)	Listed as a Carcinogen in NTP, IARC or OSHA 1910(z) (specify)
None	100	Walnut Shell	No

SECTION III – PHYSICAL DATA

BOILING POINT ____ °F ____ °C	N.A.	SPECIFIC GRAVITY (H ₂ O=1)	1.0		
MELTING POINT ____ °F ____ °C	N.A.	PERCENT VOLATILE BY VOLUME (%)	N.A.	PERCENT SOLID BY WEIGHT (%)	100
VAPOR DENSITY (AIR=1)	N.A.	EVAPORATION RATE (=1)	N.A.		
SOLUBILITY IN WATER	Nil	PH=	N.A.		
APPEARANCE AND ODOR	Brown Granules, No Specific Odor			MATERIAL FORM:	Solid

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

May burn if exposed to source of ignition.	FLAMMABLE LIMITS	LEL N.A.	UEL N.A.
EXTINGUISHING MEDIA	CO ₂ , Foam or Water Fog		
SPECIAL FIRE FIGHTING PROCEDURES	Do not use high pressure stream which may spread fire. Firefighters should wear self contained breathing apparatus.		
UNUSUAL FIRE AND EXPLOSION HAZARDS	High concentrations of dust could form explosive mixture with air.		

SECTION V – HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE – Conditions to Avoid	THRESHOLD LIMIT VALUE PERMISSIBLE EXPOSURE LIMIT <input style="width: 30px;" type="text"/> <input style="width: 30px;" type="text"/>
Mechanical injury to eyes and/or skin can occur. Excessive dust inhalation may be harmful.	
PRIMARY ROUTES OF ENTRY <input checked="" type="checkbox"/> Inhalation <input checked="" type="checkbox"/> Skin Contact <input checked="" type="checkbox"/> Other (specify) Eye Through mechanical contact only.	
EMERGENCY AND FIRST AID PROCEDURES In case of irritation flush eyes or skin with water. In case of excessive inhalation of dust remove to fresh air. Call physician if necessary.	

SECTION VI – REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID Sources of ignition.
	STABLE	X	
INCOMPATIBILITY(materials to avoid)		No specific incompatibility.	
HAZARDOUS DECOMPOSITION PRODUCTS		Thermal decomposition may release smoke, Carbon Dioxide and Carbon Monoxide.	
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID N.A.
	MAY NOT OCCUR	X	

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Keep away from open flame sparks and hot surfaces.	
Sweep or vacuum up and place waste in disposal container.	
WASTE DISPOSAL METHOD Disposal must be made according to Federal, State and Local regulations.	
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs) N.A.	
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33) N.A.	
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water) N.A.	
<input type="checkbox"/> Theoretical _____ lb/gal	<input type="checkbox"/> Analytical _____ lb/gal

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify Type) Provide adequate ventilation. NIOSH/MSHA approved respiratory protection as required.		
VENTILATION	LOCAL EXHAUST (Specify Rate) As required for specific user application.	SPECIAL
	MECHANICAL (General – Specify Rate) See Section IX "Other Precautions"	OTHER
PROTECTIVE GLOVES (Specify Type) Normal Work Gloves		EYE PROTECTION (Specify Type) Safety Goggles
OTHER PROTECTIVE EQUIPMENT Special protection is required for workers exposed to abrasive blast operation.		

SECTION IX – SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Keep dry to maintain material in usable condition.	
Store in original containers to maintain identity.	
OTHER PRECAUTIONS Determine compliance with OSHA 1910.1000 Table Z-3 "Inert or Nuisance Dust"	
PEL – Total Dust: 15 mg/m ³ Respirable Fraction: 5 mg/m ³	
N.A. = Not Applicable mg/m ³ = milligrams per cubic meter PEL= Permissible Exposure Limit, 8 hr. Time Weighted Average	

<p>Maxi-Blast[®] Inc.</p> <p>3650 North Olive Road – South Bend, In 46628 (574) 233-1161 – Fax: (574) 234-0792 – e-mail: info@maxiblast.com MSDSWS Page 2 Rev. – 6 1/31/08</p>	
---	--